

# TransferRite<sup>®</sup> Sign Products

## TransferRite<sup>®</sup> **ULTRA<sup>®</sup>**

- A product with a "U" in the code means adhesion to exposed liner
- Reduces tunneling and dog-eared corners
- Ideal for RTA decals
- Makes for a professional-looking and profitable job

### Tack level



- The smaller the letters or graphics, the higher the tack level
- Some films are transferred more easily with high tack products

### Application tips

- Don't attempt to lift the letters—turn the graphic over and peel back the liner
- Squeegee the tape onto the graphic and the graphic onto the target surface from the center out
- Remove the tape from the applied graphic by peeling back on itself at a 45° angle

### Sign protection

- Protect a sign in the crate, during transportation and while it's sitting in the yard or on the job site
- For the protection of finished signs, for example a painted cabinet with a vinyl-decorated face
- ProtectRite 8510 is engineered for 6 month outdoor durability



ActionSign  
Group,  
Lenoir, NC



Color coded extended cores denote tack level and keep the rolls' edges from getting nicked.



Peel the paper backing away from the graphic to ensure successful transfer.

# TransferRite<sup>®</sup>

By  **ABI Tape**

# Product Selection Guide: Sign

PRODUCT NUMBER	TACK LEVEL	THICKNESS PSTC-33 (mils)	ELONGATION PSTC-31 (%)	PRODUCT HIGHLIGHTS AND RECOMMENDED USES
560U	Low	4	2%	Superior adhesion to liner; For use on poster board and card stock
582U	Medium	4	2%	Superior adhesion to liner; Medium tack workhorse for general use
592U	High	4	2%	Superior adhesion to liner; Recommended for use with intermediate or calendered films
782U	Medium	5	6%	Superior adhesion to liner; Medium tack premium workhorse; Performs well in wet applications
6798	Very High	6	5%	Recommended for use with reflective films, awning material and etched glass films
1310	Medium	4	750%	Ultra clear film with Ultra adhesive for drop shadows and multicolor alignments; Tears easily; Doesn't grab banner material or corrugated plastic; Recommended for use with intermediate and calendered films
1320	High	4	750%	Ultra clear film for use with SignGold, etched glass films; Recommended for tiny lettering and graphics
1510	Medium	4	570%	Frosted clear film for drop shadows and multicolor alignments
7505	Medium	5	380%	Reusable film for use in application frames
8510	Medium	3	500%	Outdoor durable, UV-resistant (up to 6 months) blue film for finished sign protection

**Applications recommendations** - the performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American Bilrite Inc. assumes no liability for claims beyond the replacement value of any defective products, and is in no way liable for consequential or incidental damages. These products (unless otherwise noted) are not suitable for prolonged outdoor exposure.



105 Whittendale Drive • Moorestown, NJ 08057  
 PH: (856) 778-0708 • FAX: (856) 778-7485  
 Toll Free Fax: 888-224-6325 (US Only)

[WWW.ABITAPE.COM](http://WWW.ABITAPE.COM)