

## Product Design

TransferRite 1510 is a unique clear polypropylene film backing with a custom formulated latex pressure sensitive adhesive for decal transfer and pre-spacing.

## Application

TransferRite 1510 is used where precise registration is required and designed to assist in the application of pressure sensitive decals that have been cut into letters and legends. 1510 works well with pre-spaced lettering 2" - 12" high, as well as decals or lettering < 12" in one dimension. 1510 can also be used on printed or unprinted graphics.

## Performance Features

- ☑ Transparency is ideal for fine, detailed inlays or overlays, or applications requiring **precise registration**
- ☑ **Dimensionally stable**, maintains alignment and resists stretching, folding or sagging during installation
- ☑ **Moisture resistant** under conditions of long term storage

Physical Properties	Values
Colors	Clear
Nominal Thickness	4.2 mils (.11 mm)
Adhesion (@90°)	8.5 oz/in (2.3 N/25mm)
Tensile Strength	24 lb/in (105 N/25mm)
Elongation (%)	570

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be constructed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective.

Sc1510/0618

