

Product Design

TransferRite Ultra 592U is a high grade saturated paper backing with superior adhesive technology designed for use over ready-to-apply graphics or where large areas of exposed liner are present. This product offers superior adhesion to liner.

Application

TransferRite Ultra works well with printed and unprinted graphics and with pre-spaced lettering under 2" high. 592U can also be used for fine line striping and ready-to-apply graphics.

Performance Features

- ☑ Demonstrates superior **adhesion to liner** technology
- ☑ **Lays flat** to eliminate "dog-eared" decals
- ☑ **Trouble-free** stacking and storage of masked graphics
- ☑ **Reduces** wrinkling, tunneling & edge lifting

Physical Properties	Values
Color	White
Nominal Thickness	4.3 mils (.11 mm)
Peel Adhesion @90°	9 oz/in (2.5 N/25mm)
Tensile Strength	21 lb/in (92 N/25mm)
Elongation	2%

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be constructed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective.

Cv592U/0618

