

2401-a Corporate Blvd Brooksville, FL 34604 Tel: 352-593-4151 Fax: 352-796-4437



sales@mbs-sign.us

Material Safety Data Sheet

Quick Snap Glue 1

1- Chemical Product and Company Identification:

Product Name: Quick Snap Glue 1 Product Type: Cyanoacrylate Ester Date revised: 08/01/08 **Emergency Number: 800-535-5053**

2- Composition/Information on Ingredients:

% Hazardous Component CAS Number Ethyl-2 Cyanoacrylate 7085-85-0 80-95 Poly Methyl Methacrylate 9011-14-7 5-10

Exposure Limits (TWA) ACGIH (TLV) OSHA (PEL) <u>OTHER</u>

Ethyl-2 Cyanoacrylate None None 0.2 ppm

3- Hazards Identification:

Potential Health Effects:

Inhalation: Exposure to vapors above the established exposure limit results in respiratory

irritation which may lead to difficulty breathing and tightness in the chest.

Skin Contact: Bonds to skin in seconds. May cause skin irritation. Cyanoacrylates have been

reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacrylates generate heat during the

cure process and, in rare instances, a large drop can burn the skin.

Eye contact: Irritating to eyes. Causes excessive tearing. Eyelids may bond.

Ingestion: Material is not harmful if ingested. Cyanoacrylates are almost

impossible to swallow because they solidify in the mouth.

4- First Aid Measures:

Ingestion: Ingestion is unlikely. See supplemental section for emergency action. Inhalation: Remove to fresh air. If symptoms persist, obtain medical attention. Skin contact: Soak in warm water. Do not pull skin apart. See supplemental section for

emergency action.

Eye contact: Flush with warm water. If eye lids are bonded closed, release eyelashes with

warm water by covering the eye with a wet pad. Do not force eye open. See

supplemental section for emergency action.

5- Fire Fighting Measures:

Flash Point: 150-200°F, Tag Closed Cup

Extinguishing Media: Foam, Dry Chemical or Carbon Dioxide

Unusual Fire or Explosion Hazards:

Special Fire Fighting Procedures: Wear self-contained breathing apparatus



2401-a Corporate Blvd Brooksville, FL 34604 Tel: 352-593-4151 Fax: 352-796-4437



sales@mbs-sign.us

6-Accidental Release Measures

Steps to be taken in case of spill or leak: Do not use cloths for clean-up. Flood spilled material

with water to polymerize. Cured material can be scraped up and disposed of as non-hazardous waste. Make sure

spill area is well ventilated.

7- Handling and Storage:

Safe storage: Store away from heat and direct sunlight to maximize shelf life. Store inside in a

dry location. Keep container tightly closed.

Handling: Avoid contact with skin, eyes, and clothing. Avoid breathing vapor or mist. Avoid contact with paper goods or fabric. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors.

8- Protective Equipment:

Ventilation: Local exhaust ventilation is recommended to maintain vapor level below TLV.

Respiratory protection: Not applicable with good local exhaust. Use NIOSH approved respirator if there is a potential to exceed exposure limits

a potential to exceed exposure limits.

Skin: Polyethylene or non reactive gloves. Do not use cotton, PVC, or wool. See

supplemental page for more information.

Eye protection: Safety glasses or goggles with side shields.

9- Physical and Chemical Properties:

Appearance: clear liquid
Odor: Sharp, irritating
Boiling Point: Greater than 300°F
Melting Point: Not determined

Vapor Pressure: Less than 0.5mm Hg @25°C

pH: Not applicable

Vapor Density: Approximately 3 (Air =1)

Evaporation rate: Not applicable Specific Gravity: 1.06 at 20° C Odor Threshold: 1-2 ppm

Solubility in water: Negligible. Polymerized by water.

Partition coefficient: Not determined

Volatile Organic Compound:

(SCQAMD Method 316B) less than 20 grams per liter (estimated)

10- Stability and Reactivity

Stability: Stable under recommended storage conditions.

Hazardous Polymerization:

Rapid exothermic polymerization will occur in the presence of water,

amines, alkalis

and alcohols.

Incompatibility: Polymerized by contact with water, alcohols, amines, and alkalis.

11- Toxicological Information

Acute oral LD50 >5000mg/kg (rat) (estimated). Acute dermal LD50> 2000 mg/kg (rabbit) (estimated).



2401-a Corporate Blvd Brooksville, FL 34604 Tel: 352-593-4151 Fax: 352-796-4437



sales@mbs-sign.us

12-Ecological Information

No Data

13- Disposal Considerations:

Disposal procedures: Dispose of in accordance with Federal, State and local regulations.

14- Transportation Information:

Domestic Ground Transport:

Proper shipping name: Combustible liquid, n.o.s. (more than 450 liters)
Hazard class or division: Combustible liquid (more than 450 liters)

Identification number: NA 1993 (More than 450 liters)

Exceptions: Unrestricted under 450 liters

Marine pollutant: No

International Air Transportation (ICAO/IATA):

Proper shipping name: Aviation regulation liquids, n.o.s. (Cyanoacrylate ester)

Hazard class or division:

Identification number: UN 3334 Packing Group: None

Water transportation (IMO/IMDG):

Proper shipping name: Unrestricted

Hazard Class or Division:
Identification number:
Packing Group:
Marine pollutant:
None

15- Regulatory Information

TSCA 8b Inventory status: All components are listed or exempt

CERCLA/SARA Section 302 EHS: None

CERCLA/SARA Section 311/312: Immediate health hazard, Delayed health hazard, Fire, Reactive

CERCLA SARA 313: None California Proposition 65: None

Canada DSL/NDSL: All components are listed or exempt

WHMIS hazard class: B.3, D.2.B

16- Other Information

Hazard NFPA	Hazard Code®	HMIS Hazard Code®	
Health	2	2	
Fire	2	2	
Physical Hazard:	1	1	
Specific Hazard	No water	Personal protection: See Section	า 8



2401-a Corporate Blvd Brooksville, FL 34604

Tel: 352-593-4151 Fax: 352-796-4437



sales@mbs-sign.us

First Aid Supplement

Cyanoacrylate adhesive is a very fast setting and strong adhesive. It bonds human tissue and skin in seconds. Experience has shown that accidents due to Cyanoacrylates are best handled by passive, non-surgical first aid. Treatment of specific types of accidents are suggested as follows:

Skin Contact- Remove excess adhesive. Soak in warm, soapy water. The adhesive will come loose from the skin in several hours. Dried adhesive does not present a health hazard even when bonded to the skin. Avoid contact with clothes, fabric, rags or tissue. Contact with these materials may cause polymerization. The polymerization of large amounts of adhesive will generate heat causing smoke, skin burns, and strong, irritating vapors. Wear rubber or polyethylene gloves and an apron when handling large amounts of adhesive.

Skin Adhesion- First immerse the bonded surfaces in warm, soapy water. Peel off or roll the surfaces open with the end of a blunt edge, such as a spatula or a spoon handle, then remove adhesive from the skin with soap and water. Do not try to pull the surfaces apart with a direct opposing action.

Eyelid Adhesion- In the event that eyelids are stuck together or bonded to the eyeball, wash thoroughly with warm water and apply a gauze patch. The eye will open without further action, typically in one to two days. There will be no residual damage. Do not try to open the eyes by manipulation.

Adhesive in eye- Adhesive introduced into the eyes will attach itself to the eye protein and will disassociate from it over intermittent periods, usually in several hours. This will cause periods of weeping until clearance is achieved. It is important to understand that disassociation will normally occur within a matter of hours, even with gross contamination.

Mouth- If lips are accidentally stuck together apply lots of warm water and encourage maximum wetting and pressure from saliva inside the mouth. Peal or roll lips apart. Do not try to pull the lips with direct opposing action. It is almost impossible to swallow Cyanoacrylate. The adhesive solidifies and adheres in the mouth. Saliva will lift the adhesive in one to two days.

Burns- Cyanoacrylates give off heat on solidification. In rare cases, large drops will increase in temperature enough to cause a burn. Burns should be treated normally after the lump of Cyanoacrylate is released from the tissue as described above.

Surgery- It should never be necessary to use such drastic action to separate accidentally bonded skin.

Prepared by: Mbs-Sign Regulatory Department

Company: Mbs-Sign Revision Date: 08/01/08