

KONG® Spec Sheet

01/2023

UV PolyCarb Pressure Sensitive 15 Mil Polycarbonate overlaminate w/ Optically Clear RD-60A, Permanent Adhesive - 3" Core

Benefits

Velvet surface hides scratches and fingerprints.

Physical Properties

Thickness	15 Mil	Conversion	Cold	
Material	Polycarbonate	Core 3"		
Finish	Matte	Durchilitu	Indoor: 3 year	
Adhesive	Permanent	Durability	Outdoor: 2 year	

Film Type

Calendered



Description

Our 15 Mil PS UV Polycarb is an extremely durable heavy weight finish with a UV enhanced, permanent, polyacrylic adhesive. Backed with a polyester release liner, it works well with both indoor or outdoor applications.

Applications

Indoor & Outdoor Signage	Window Graphics		
Retail POP/POS Signage	Building Signs		
Trade Show Graphics	Posters & Decals		

Available Sizes

Widths (inch)				Lengths (feet)			
38"	51"					75'	15

Terms and Conditions

Information on physical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of any material for their specific use. All technical data is subject to change without prior notice.



mbs-signsupply.com