



6 Mil Pressure Sensitive Textured Floor Lamination - 3" Core

Benefits

UL Anti Slip Rated, Economical, Ultra Clear Visibility.

Physical Properties

| | | | |
|-----------|-----------|------------|------------------|
| Thickness | 6 Mil | Conversion | Cold |
| Material | PVC | Core | 3" |
| Finish | Matte | Durability | Indoor: 1 year |
| Adhesive | Permanent | | Outdoor: 6 month |

Film Type

Calendered

Applications

| | |
|---------------------------------|---------------------|
| Short Term Interior Floors | Trade Show Graphics |
| Floor & Counter Top Advertising | |
| Sealed Concrete Floor Graphics | |



Description

This PVC textured laminate was specially designed to be a protective overlay for virtually any substrate with high tack adhesive to create a temporary Floor advertisement. Formulated solvent acrylic adhesive for a strong bond and exceptional clarity. UL rated (UL410 SA34033) for anti-slip properties.

Available Sizes

| Widths (inch) | | | | | Lengths (feet) | |
|---------------|-----|--|--|--|----------------|--|
| 38" | 54" | | | | 150' | |
| | | | | | | |

Terms and Conditions

Information on physical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of any material for their specific use. All technical data is subject to change without prior notice.



mbs-signsupply.com
5046 W Linebaugh Ave, Tampa, FL 33624
contact@mbs-signsupply.com
+1 (303) 935-8565