



5 Mil High Performance, Low Melt, UV Protected Gloss Laminate - 3" Core

Benefits

Economical, ultra clear visibility.

Physical Properties

Thickness	5 Mil	Conversion	Thermal
Material	Vinyl	Core	3"
Finish	Gloss	Durability	Indoor: 1 year
Adhesive	Permanent		Outdoor: 6 month

Film Type

Cast	Temperature	170°F to over 245°F
------	--------------------	---------------------

Applications

Indoor & Outdoor Signage	Window Graphics
Retail POP/POS Signage	Building Signs
Trade Show Graphics	Posters & Decals

Terms and Conditions

Information on physical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of any material for their specific use. All technical data is subject to change without prior notice.



Description

3 mil Polyester Primer 2 mil Co-extrusion, High performance, low processing temperature, U.V. protected, thermal laminating film engineered for wide format applications on both ink jet and electrostatic prints.

Available Sizes

Widths (inch)					Lengths (feet)	
25"	38"	43"	51"	55"	250'	
62"						



mbs-signsupply.com

5046 W Linebaugh Ave, Tampa, FL 33624

contact@mbs-signsupply.com

+1 (303) 935-8565

© 2023 Mbs-Signsupply. All rights reserved. All other product and brand names are trademarks or registered trademarks of their respective owners.